



Mitsubishi Chemical America, Inc.

Product Bulletin


Description

Hostaphan® 42DI is a clear polyester film that is chemically primed on one side to promote adhesion of *indigo*® liquid toner inks, and chemically primed on the opposite side to promote slip and improve handling. It combines high strength, durability, and optical clarity.

Performance

Hostaphan® 42DI is designed for markets requiring clarity, ink adherability and surface properties necessary for singulation and collation. Hostaphan® 42DI is used for digital liquid toner printing.

Schematic of Hostaphan® 42DI



Benefits

- One side chemically primed for liquid toner
- Opposite side chemically treated to provide the surface necessary for colation and singulation from a stack of sheets
- · Excellent color and clarity
- Most dry erase markers can be wiped off slip side

Typical Properties of Hostaphan® 42DI Film

The Hostaphan® 42DI property values below are typical measurements. Further guidance on series selection, functional behavior by end use, film processing, standard roll configuration and gauges is available through a Polyester Film Sales Representative.

Property		Unit of Measure	Т	ypical Value	Test Method
Area Yield		in²∙mil/lb m²∙µm/kg		19,800 717	ASTM D 4321
Tensile Strength	MD	psi kg/cm²		30,000 2,110	ASTM D 882
Yield Strength (F5)	MD	psi kg/cm²		15,000 1,050	ASTM D 882
Ultimate Elongation	MD	%		140	ASTM D 882
Modulus	MD	psi kg/cm²		500,000 35,200	ASTM D 882
Coefficient of Friction A/B	Kinetic			TBD	ASTM D 1894
Shrinkage	MD TD	%		1.0 0.0	30 min. at 150°C
Density		g/cm³		1.3975	ASTM D 1505
Total Haze*		%	300 gauge	2.0	ASTM D-1003

^{*} Values for reference data only. Contact a Polyester Film Sales Representative for actual gauges available. Approved DJ 1/2009

Mitsubishi Chemical America, Inc. • PO Box 1400 • 2001 Hood Road • Greer, SC 29652 • 864-879-5000 • 864-879-5006 • www.m-petfilm.com

Hostaphan is a registered trademark of Hoechst AG and is licensed to Mitsubishi Chemical America, Inc. The information contained herein is believed to be true and accurate, but all data, recommendations and suggestions are provided without guarantee, since the conditions of use are beyond our control and can affect the performance and properties of our products. The user is solely responsible for confirming that our product is suitable for the intended end use, and for compliance with all legal regulations and patents. Other than compliance with published Mitsubishi Chemical America, Inc. specifications for one year following purchase, if properly handled, and except as required by law, MITSUBISHI CHEMICAL AMERICA, INC. MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR ANY WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If a product is found to be non-conforming during the warranty period, user's sole remedy and our sole obligation is, at our option, replacement of the affected product or refund of the purchase price. Except as required by law, we are not liable for any damage, harm or loss resulting from our product, whether direct, indirect, consequential, incidental or special, and irrespective of legal theory asserted, including strict liability, contract, warranty, or negligence.